




## Light Source Technical DataSheet

EAN	<b>3276007960716,3276007960556,3276007960563</b>
Product Supplier reference	<b>8820 CCT,8820 CCT-W,8820-34 CCT</b>
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	INSPIRE
Replaceability of Light source	by qualified person
Light sources maker model	<b>TL8820D CCT</b>
Link to EU Product Data base	<a href="https://eprel.ec.europa.eu/screen/product/lightsources/2402266">https://eprel.ec.europa.eu/screen/product/lightsources/2402266</a>
Spectral power distribution in the range 250 nm to 800 nm. at full-load	 <p>The graph shows the spectral power distribution (SPD) of the light source. The x-axis represents wavelength in nanometers (nm) from 380 to 780. The y-axis represents relative power from 0.0 to 1.2. A sharp blue peak is visible at approximately 450 nm, and a broader red peak is visible at approximately 650 nm. A rainbow spectrum is overlaid on the graph, and the text '1.0 = 5.01lm/100lm' is present in the top right corner.</p>
The reference control settings, and instructions on how they can be implemented, where applicable	
If the light source contains mercury: instructions on how to clean up the debris in case of accidental breakage	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for advice on recycling.

