

## DECLARATION OF PERFORMANCE

No: 007

1. Unique identification code of the product

DRY-PRESSED CERAMIC TILES WITH THICKNESS <7,5MM, WITH WATER ABSORPTION  $E \leq 0,5\%$ , TYPE 7

2. Intended use

FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS

3. Name and address of Manufacturer

BALDOCER, S.A.  
Ctra. La Pobla Tornesa – Vall d’Alba, km.4  
12192 Vilafamés (Castellón) SPAIN

4. Systems of AVCP: System 4

5. Harmonised standard: EN 14411: 2012

6. Declared performances

ESSENTIAL CHARACTERISTICS	PERFORMANCES
Reaction to fire	A1 <sub>FL</sub> -A1
Release of dangerous substance, for: - Cadmium - Lead - Others	NPD
Breaking strength	$\geq 700$ N
Slipperiness, as: PTV (wet) slider 57, CEN/TS 16165:2012 Annex C	NPD
Bond strength/adhesion, for: - Cementitious adhesives - Dispersion adhesives - Reaction resin adhesives - Mortar	Type C2: $> 1$ N/mm <sup>2</sup> NPD NPD NPD
Thermal shock	Pass
Durability for: - Internal use - External Use: freeze-thaw resistance	Pass Pass
Tactility	NPD

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Felipe Peraire Palos  
General Manager

Vilafamés, October 8th 2020