



	Light Source Technical DataSheet
EAN	3276007963427
Product Supplier reference	T089-C-3030120-B
Supplier's name or trade mark	INSPIRE
Why the replacement of light sources and/or separate control gear is not appropriate ?	No spare part available
Light sources maker model	T089-C-3030120-W-LS
Useful luminous flux (lm)	4000
Correlated colour temperature (K)	2700
Correlated colour temperature (K)	4000
Correlated colour temperature (K)	6200
Correlated colour temperature (K)	
On-mode power (W)	23.5
Standby power (W)	N/A
Colour rendering index	80
Spectral power distribution in the range 250 nm to 800 nm. at full-load	
References to the harmonised normes and standards	(EU) 2019/2020 (EU) 2019/2015 (EU) 2021/340 (EU) 2021/341
Testing conditions if not described sufficiently in previous harmonised standards	Not Applicable
Calculations performed with the parameters	$\eta_{TM} = (\phi_{USE} / P_{ON}) \times F_{TM}$
With FTM =	0.926
The reference control settings, and instructions on how they can be implemented,	The light source of the product can be set to different CCT: 2700K or 4000K or 6200K by dip switch
Specific precautions that shall be taken when the model is assembled. installed. maintained	No specific precautions
Instructions on how to remove LED Module	
Step 1 Picture Tools	Remove the back panel.  screwdriver
Step 2 Picture Tools	Remove the pearl cotton, light guide plate, reflective paper and lampshade.  by hand
Step 3 Picture	Fix the light source on sides of the frame. 
Step 4 Picture Tools	