



# Light Source Technical DataSheet

EAN	3276007963342
Product Supplier reference	T088-C120K1-PN5
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	INSPIRE
Replaceability of Light source	non-replacable
Replaceability of separate control gears	by qualified person
Light sources maker model	T088-C120K1-WN5-LS
Link to EU Product Data base	<a href="https://eprel.ec.europa.eu/screen/product/lightsources/2470367">https://eprel.ec.europa.eu/screen/product/lightsources/2470367</a>
Spectral power distribution in the range 250 nm to 800 nm. at full-load	
The reference control settings, and instructions on how they can be implemented,	The light source of the product can be set to different CCT: 2800K or 4400K or 6800K by dip switch. The reference control
If the light source is dimmable: a list of dimmers it is compatible with, and the light	DIP switch for color temperature
If the light source contains mercury: instructions on how to clean up the debris in	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for
Driver maker model	SEN008S0070WD01
Maximum output power of the driver (for HL, LED and OLED) or the power of the light source for which the driver is intended (for FL and	5.7
Type of light source(s) for which it is	LED
Efficiency in full-load	79.40%
No-load power (Pno) (W)	N/A
Standby power (Psb) (W)	N/A
Standby power (Pnet) (W)	N/A
Driver suitable for dimming :	no

