

EAN	BRAND	SUPPLIER REFERENCES	LIGHT SOURCE REFERENCES	REGISTRATION NUMBER	SUPPLIER	Techxin Electric Appliance Manufacture Co., Ltd
3276007973303	INSPIRE	TX-36DL01-V5(WH)	TX1400012-340mA	2480264	PROJET NAME :	
3276007973334	INSPIRE	TX-36DL01-V5(WD)	TX1400012-340mA	2480264	PROJECT CODE :	2026R13P02
3276007973358	INSPIRE	TX-44DL01-V5(WH)	TX1400012-340mA	2480264		
3276007973341	INSPIRE	TX-44DL01-V5(WD)	TX1400012-340mA	2480264		
3276007995398	INSPIRE	TX-44DL01-V5(BK)	TX1400012-340mA	2480264		



## Light Source Technical DataSheet

Registration informations	
EAN	3276007973303,3276007973334,3276007973358,3276007973341,32760079398
Product Supplier reference	#N/A
Creation date (dd/mm/yyyy)	12/11/2025
Last update date (dd/mm/yyyy)	12/11/2025
Product informations	
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	#N/A
Date of placement on the market (YYYY-MM-DD)	
Replaceability of Light source	by qualified person
Does the light source work with a separate driver or PCB?	yes
Light source Informations	
Light sources maker model	#N/A
Equivalent models already placed on the market	TX-36DL01-V4/TX-44DL01-V4
EPREL registration informations	
EPREL Registration number	#N/A
Link to EU Product Data base	#N/A
Type of light source	
Lighting technology used	LED
Non-directional (NDLS) or directional (DLS)	NDLS
Light source cap-type	Connector
Mains (MLS) or non-mains (NMLS)	NMLS
Connected light source (CLS)	No
Colour-tunable light source	No
High luminance light source	No
Anti-glare shield	No
Dimmable	only with specific types of dimmable light sources
General light source parameters	
Energy consumption in on-mode (kWh/1000h)	11
Useful luminous flux (lm)	2200
Beam angle correspondence (degrees)	360
Energy Efficiency Class	B
Correlated colour temperature type (K)	range
Correlated colour temperature (K)	6500
Correlated colour temperature (K)	
Correlated colour temperature (K)	
On-mode power (W)	11.0
Standby power (W)	
Colour rendering index	80
Outer dimensions (Height) (millimetre)	581
Outer dimensions (Width) (millimetre)	11
Outer dimensions (Depth) (millimetre)	1
Spectral power distribution in the range 250 nm to 800 nm. at full-load	
Spectral power distribution (picture name)	#N/A
Claim of equivalent power	
Chromaticity coordinate (x)	0.313
Chromaticity coordinate (y)	0.337
Parameters for LED and OLED light sources	
R9 Colour rendering index	30
Survival factor	0.90
Lumen maintenance factor	0.96
Other informations	
References to the harmonised normes and standards	(EU)2019/2020 (EU)2019/2015 (EU)2021/340 (EU)2021/341
Testing conditions if not described sufficiently in previous harmonised standards	Not Applicable
Calculations performed with the parameters	$\eta_{TM} = (\phi_{USE} / \text{PON}) \times \text{FTM}$
The reference control settings, and instructions on how they can be implemented, where applicable	
Specific precautions that shall be taken when the model is assembled, installed, maintained or tested	No specific precautions
If the light source contains mercury: instructions on how to clean up the debris in case of accidental breakage	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for <a href="#">advice on recycling.</a>
Instructions on how to remove LED Module and/or Driver	
<b>Step 1</b>	By hand, rotate 60° counterclockwise to remove the lampshade
Picture	
Tools	By hand, rotate 60° counterclockwise to remove the lampshade
<b>Step 2</b>	Disconnect the terminal
Picture	
Tools	By hand
Tools	By hand