

# FRONTAL DE INSPECCIÓN USB RECARGABLE

### Características de Producto

- Encendido/Apagado mediante interruptor. Sensor/PIR para la función de "Manos libres".
- Orientable hasta 60° para múltiples aplicaciones.
- 5 modos de funcionamiento – 100%, 50%, Intermitente, Luz roja y Rojo Intermitente.
- Recargable USB.
- Ligero y resistente.
- Cinta para cabeza ajustable.
- Batería de 3 horas de duración a máxima potencia, 20 horas a mínima.
- Suministrado con cable USB. 50cm.



| CAT NO.   | LUMINARIA (LÚMENES) | POTENCIA (W) | TIEMPO DE CARGA (HRS) |
|-----------|---------------------|--------------|-----------------------|
| LILH17P65 | 170                 | 3W           | 3 Hours               |

| CAT NO.   | EFICIENCIA (LLM/W) | PESO (KG) | DIMENSIONES (MM) | TIPO BATERÍA | BATTERY CAPACITY | CRI | RATIO IK | RANGO TEMP. (°C) | TEMP. AMBIENTE V.UTIL (°C) |
|-----------|--------------------|-----------|------------------|--------------|------------------|-----|----------|------------------|----------------------------|
| LILH17P65 | 56.66              | 0.07      | 60x37x45mm       | 3.7V Li-Ion  | 1200mAh          | >80 | IK05     | -20 to +25       | 25                         |



Modo Luz roja  
100% – Flash



Modo Luz blanca  
100% – 50% – Flash



| STANDARD  | DESCRIPTION                                                                                                         |
|-----------|---------------------------------------------------------------------------------------------------------------------|
| 60598-1   | Luminares – General requirements                                                                                    |
| 60598-2-4 | Luminares – Portable                                                                                                |
| 61000-3-2 | Electromagnetic compatibility (EMC) – Part 3-2: Limits – for harmonic current emissions                             |
| 61000-3-3 | Lamp controlgear – Part 1: General and safety requirements                                                          |
| 61547     | Equipment for general lighting purposes – EMC immunity requirements                                                 |
| 55015     | Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment |