

## Supplier self-declaration form of the packaging conformity to the TR CU 005/2011

We, manufacturer (or representative entity) *Full legal name, full legal address, country*, declare under our sole responsibility that the production range packaging below conforms to the Technical Regulation of Customs Union 005/2011 in it's last version.

List of references :

<b>EAN</b>	<b>Supplier reference</b>	<b>Type of packaging (ex: carton box, metal can)</b>	<b>Country of origin of the packaging</b>	<b>Packaging materials</b>
8421807090216	09021	paper/carton packaging	spain	paper
8421807588027	58802	paper/carton packaging	spain	paper
8421807588126	58812	paper/carton packaging	spain	paper

8421807090124	09012	paper/carton packaging	spain	paper
8421807610209	61020	paper/carton packaging	spain	paper
8421807090209	09020	paper/carton packaging	spain	paper
8421807798006	79800	paper/carton packaging	spain	paper
8421807580144	58014	paper/carton packaging	spain	paper

8421807090223	09022	paper/carton packaging	spain	paper
8421807610407	61040	paper/carton packaging	spain	paper
8421807615501	61550	paper/carton packaging	spain	paper
8421807610117	61011	paper/carton packaging	spain	paper
8421807588010	58801	paper/carton packaging	spain	paper
		paper/carton packaging	spain	paper

8421807088763	08876	paper/carton packaging	spain	paper
8421807588102	58810	paper/carton packaging	spain	paper
8421807088718	08871	paper/carton packaging	spain	paper
8421807088701	08870	paper/carton packaging	spain	paper
8421807090117	09011	paper/carton packaging	spain	paper
8721807090088	09008	paper/carton packaging	spain	paper

8721807090187	09018	paper/carton packaging	spain	paper
8421807090001	09000	paper/carton packaging	spain	paper
8721807090194	09019	paper/carton packaging	spain	paper
8421807110419	11041	paper/carton packaging	spain	paper
8721807090095	09009	paper/carton packaging	spain	paper
		paper/carton packaging	spain	paper

8421807090100	09010	paper/carton packaging	spain	paper
8421807615518	61551	paper/carton packaging	spain	paper
8421807610315	61031	paper/carton packaging	spain	paper
8421807088756	08875	paper/carton packaging	spain	paper
8721807090071	09007	paper/carton packaging	spain	paper

8721807090170	09017	paper/carton packaging	spain	paper
8421807610100	61010	paper/carton packaging	spain	paper
8421807111348	11134	paper/carton packaging	spain	paper
8421807088602	08860	paper/carton packaging	spain	paper
8421807088626	08862	paper/carton packaging	spain	paper
		paper/carton packaging	spain	paper

8721807090064	09006	paper/carton packaging	spain	paper
8721807090163	09016	paper/carton packaging	spain	paper
8421807588126	58812	paper/carton packaging	spain	paper
8421807319003	31900			
8421807319133	31913			

8421807319102	31910			

REQUIREMENTS FOR PACKING based on TR CU 005					
Type of packaging	Requirement	Value specified by the manufacturer	Attempted value	Regulation	reference list of standarts
metal packaging	must ensure tightness at internal overpressure of air			TR CU 005 p.5 (6.1)	Test method can be specified by the manufacturer

	must withstand the compressive force in the direction of the vertical axis of the package box				
	the inner lining must be resistant to the product being packaged and (or) withstand sterilization or pasteurization in simulated environments				
	resistant to corrosion				
polymeric packaging	must ensure tightness; - must withstand the specified number of impacts during free fall from a height without destruction (for sealed products, <b>except perfumery and cosmetic products</b> )	1278mN	1278mN	<b>TR CU 005 p.5 (6.3)</b>	Test method can be specified by the manufacturer
	must withstand the compressive force in the direction of the vertical axis of the package body ( <b>except polybags</b> )				

	should not deform and crack when exposed to hot water ( <b>except polybags</b> )				Test method can be specified by the manufacturer
	the packaging handles must be firmly attached to it and withstand the specified load;	21.4mPa	21.4mPa		
	the welded and glue seams of the packaging must not allow water to pass through	610%	610%		
	must withstand the established static tensile load ( <b>polybags only</b> );	610%	610%		
paper/carton packaging	must withstand the specified number of impacts during free fall and (or) when tested for horizontal impact	100.000	100.000	<b>TR CU 005</b> <b>p.6.4</b>	GOST ISO 2234-2014 (based on ISO 2234:2000)- Stacking tests using a static load GOST ISO 2244-2013 (based on ISO 2244:2000) Horizontal impact test methods
	must withstand the compressive force in the direction of the vertical axis of the package body and (or) provide strength	Si	si		

	when stacked;				
	packaging handles (if any) must be firmly attached to the packaging and must be able to withstand the specified load	si	si		
combined materials	must be airtight (in the presence of closures) or ensure the established strength of the joint seams			TR CU 005 p.6.5	GOST ISO 1924-1-96 - Paper and board. Determination of tensile properties. Part 1. Constant rate of loading method
	the surface of the inner coating must not be oxidized				
	the inner surface of the package must be resistant to the effects of the product being packaged.				

textile packaging	must withstand the specified number of impacts during free fall from a height without destruction			TR CU 005 p.6.6	Test method can be specified by the manufacturer
	must withstand the specified breaking load.				
wood packaging	must withstand the specified number of impacts during free fall from a height without destruction			TR CU 005 p.6.7	GOST ISO 2234-2014 (based on ISO 2234:2000)- Stacking tests using a static load GOST ISO 2244-2013 (based on ISO 2244:2000) Horizontal impact test methods GOST 18211-2018 (based on ISO 12048:1994)- Transport packages. Compression test method
	must withstand the specified number of impacts on horizontal or inclined planes				
	must withstand the compressive force in the direction of the vertical axis of the package body				
	the moisture content of the wood must correspond to the established				

ceramic packaging	must be waterproof			<b>TR CU 005 p.6.8</b>	Test method can be specified by the manufacturer
	must be airtight when sealed				
glass packaging	must withstand internal hydrostatic pressure, depending on the main parameters and purpose			<b>TR CU 005 p.6.2</b>	Test method can be specified by the manufacturer
	must withstand temperature differences without destruction				
	must withstand a compressive force in the direction of the vertical axis of the package body (except bottles)				
	water resistance of glass must be at least 3/98 class (for food products, including baby food, perfumery and cosmetic products)	N/A	N/A		
	Must be acid resistant (for cans and bottles for canning, food acids and baby food);	N/A	N/A		

should not be reused for contact with baby food	N/A	N/A		
---	-----	-----	--	--