

Transient surge protector T2 1P+N

Transient surge protection device Type 2 for single-phase lines, with 1P+N configuration, 320V AC, 15–30kA discharge capacity and 1-module format.



Features

Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)
Protection type (modular)	Transient surge protector
No. of poles	1P + N
Modules (18 mm)	1
Network type	Alternating current (ac)
Fixation	35mm DIN rail
Nominal voltage	320 Vca - (50/60 Hz)

Technical data

Fire resistance (GWEPT)	960 °C
Ambient operating temperature	-5 °C ; +40 °C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 61643-11:2013
According to Regulations IEC	IEC- 61643-11:2011

In accordance with the Low Voltage Electrotechnical Regulations (REBT)	Yes
--	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
---	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
---	-----

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

According to Regulations (RoHS)	UNE-EN IEC 63000:2022
---------------------------------	-----------------------

Logistics and packaging

Unit EAN code	8423220288478
---------------	---------------

EAN code container	8423220288478
--------------------	---------------

EAN code packaging	18423220288475
--------------------	----------------

Units packaging	1
-----------------	---

Units carton	86
--------------	----

Pallet Units	4000
--------------	------

Packaging Measurements cm	10x7,5x7,5
---------------------------	------------

Packaging Measures cm	42x25x16
-----------------------	----------

Unit weight (g)	116,8
-----------------	-------

Container Weight (Kg)	0,131
-----------------------	-------

Packaging Weight (Kg)	11,671
-----------------------	--------

Tariff code	85362010
-------------	----------

Documentation and downloads



Safety Information (0.38MB)