

Technical specifications

Specifications

Indoor units

All in one type

Model	HMA60-W	HMA100-W
General conditions		
Power source	400V 3NAC 50Hz / 230V 1AC 50 Hz	
Max. operating current (A)	20 (400V) / 29 (230V)	20 (400V) / 36 (230V)
Recommended fuse (A)	25 (400V) / 32 (230V)	25 (400V) / 40 (230V)
Wire size (Power source)	5 x 2.5mm ² (400V) / 3 x 10mm ² (230V)	
Wire size (Power source and communication cable to outdoor unit)	Min. 5 x 2.5 mm ² (PE, L, N, signal, signal)	
Power source deviation (%)	-15 – +10	
Power factor	0.99	
Pipe size refrigerant (ref) Gas	OD12.7 (1/2")	OD15.88 (5/8")
Pipe size refrigerant (ref) Liquid	OD6.35 (1/4")	OD9.52 (3/8")
Flare connection	OD6.35 (9.1mm); OD9.52 (13.2mm); OD12.7 (16.6mm); OD15.88 (19.7mm)	
Indoor unit (split type, hydro-unit)		
Immersion heater	Max. 9 kW (6kW for single-phase 230V)	
Capacity steps heater	3 (3,6,9kW) for three-phase 400V 3 (1.5, 3, 6kW) for single-phase 230V	
Pump model	Wilco-Para G 15/75	
Pump control	Variable	
Pump capacity, max. head	76 kPa (external)	
Pump capacity, max. flow	4 m ³ /h	
Pump power	5 – 75W	
Pump efficiency, max.	EEI<0,21	
Heat exchanger	ACH18-52H-F	ACH-30EQ-80H-F
Heat exchanger size	-0.9 m ²	-1.8 m ²
Pressure transmitter	0 – 4.6 MPa, deviation ±3%	
Water strainer system	0.6 mm ²	
Filter drier refrigeration system	Bi-flow 083	
Emergency thermostat	5 – 65 °C	
Thermal cut-off	92 (-6) °C or 98 (-8) °C	
Motor valve on hydraulic circuit	2 x 3-way, ball type	
Actuator	230V 50Hz	
Safety relief valve system	0.3 MPa	
Manometer gauge	0 – 0.4 MPa	
Expansion vessel	10L	
Expansion vessel, Factory precharge	0.5 +/- 0.15bar	
IP Grade	IP21	
Volume total	180L ±5%	
Volume coil	4.8L	
Area coil	1.6m ²	
Material coil	Steel untreated S235JR	
Material tank	Enamelled steel S235JR 3.0 mm	

Model	HMA60-W	HMA100-W
Miscellaneous		
Ambient area of operation (outdoor unit)	- 20 — +43°C	
Internet connection function	(Straight, cat.5e UTP) RJ45 plug	
Language	English (en), Swedish (sv), German (de), French (fr), Spanish (es), Finnish (fi), Lithuanian (Lt), Czech (cz), Polish (pl), Dutch (nl), Danish (da), Estonian (et), Latvian (lv), Russian (ru), Italian (it), Slovenian (sl), Greek (gr), Romanian (ro), Portuguese (pt)	

Technical specifications

Adapted to **RoHS** directive

Model			FDCW71VNX-W
Indoor unit heat exchanger			ACH-30EQ-80H
Power source			1 phase 230V 50Hz
Heating nominal capacity	condition 1	kW	8.00 (3.00 — 10.00)
	condition 2	kW	8.30 (2.20 — 9.50)
Heating power consumption	condition 1	kW	2.35
	condition 2	kW	1.93
COP	condition 1		3.40
	condition 2		4.30
Cooling nominal capacity	condition 1	kW	7.10 (2.00 — 7.10)
	condition 2	kW	9.00 (2.70 — 10.7)
Cooling power consumption	condition 1	kW	2.62
	condition 2	kW	2.48
EER	condition 1		2.70
	condition 2		3.62
Operation range (Outdoor air temperature)	Heating	°C	-20 — 43
	Cooling	°C	15 — 43
Operation range (Water temperature)	Heating	°C	25 — 60 (65 with immersion heater)
	Cooling	°C	7 — 25
System water flow		L/s	0.19 — 0.38
Min. system water flow at 100% circulation pump speed			0.19
Max. current		A	18
Recommended fuse rating		A	20
Starting current		A	5
Deviation, incoming supply			-15 — +10%
Max. refrigerant pipe length		m	50
Max. height difference when outdoor unit is higher		m	30
Max. height difference when outdoor unit is lower			15
Outdoor unit	Height	mm	750
	Width	mm	880(+88 with valve cover)
	Depth	mm	340(+78 with foot rall)
	Weight	kg	62
	Color		Stucco White
	IP grade		IP24
	Sound power level*1	dB(A)	64
	Sound power level(Silent mode)	dB(A)	60
	Sound power level(Max.)	dB(A)	69
	Sound pressure level	dB(A)	49
	Air flow (Cooling/Heating)	m ³ /min	50
	Type of compressor		RMT5118SWP11(Twin rotary type)
	Starting method		Direct line start
	Refrigerant oil	liter	0.68 M-MB75
	Heat exchanger		M shape fin & inner grooved tubing
	Ref control		EEV
	Defrost control		Reversing cycle
	Fan		Propeller fan x 1
	Fan motor	W	86 x 1
	Shock & vibration absorber		Rubber sleeve (for compressor)
	Electric heater (crank case/ base)	W	20/100
	Safety equipment		Internal thermostat for fan motor Abnormal discharge temperature protection
	Power and signal line from indoor unit		3 cores 3.5mm ² (Power line), 2 cores ϕ 1.6mm(Signal line)
	Refrigerant		R32
	Refrigerant volume (pipe length without additional charge)	kg (m)	1.84 (15)
	Additional refrigerant charge	kg/m	0.02
	Dimensions, refrigerant pipe	mm (inch)	Gas pipe: OD 15.88 (5/8"), Liquid pipe: OD 6.35 (1/4")
Refrigerant pipe connections		Flare	
Drain		Hole size: ϕ 20 × 3 pcs.	
Insulation for piping		Necessary (both Liquid & Gas lines)	
Part number MHIAE		PCA003F161	

Test conditions

		Water temperature	Outdoor air temperature
Heating	condition 1	45°Cout / 40°Cin	7°CDB / 6°CWB
	condition 2	35°Cout / 30°Cin	
Cooling	condition 1	7°Cout / 12°Cin	35°CDB
	condition 2	18°Cout / 23°Cin	

*1: Test condition for sound power level

Temperature condition: Heating condition 2, Low capacity

*2: Test condition for sound pressure level

Mike position 1m away in front of outdoor unit at the height of 1m

Installation requirements

Indoor unit	HMA60-W	HMA100-W
Outdoor unit	FDCW60VNX-W	FDCW71VNX-W
Highest recommended supply / return temperature	55/45°C	
Max. pressure, climate system	0.3MPa (3.0 bar)	
Max. temperature, climate system	65°C	
Max. temperature in indoor unit	65°C	
Max. temperature from external heat source	65°C	
Max. supply temperature with compressor	58°C	60°C
Min. supply temperature cooling	7°C	
Max. supply temperature cooling	25°C	
Min. volume, climate system without under floor cooling application	50L	80L
Min. volume, climate system with under floor cooling application	50L	80L
Max. flow, climate system	0.29L/s	0.38L/s
Min. flow, climate system	0.09L/s	0.19L/s
Nominal system flow heating ($\Delta T=5K$)	0.29L/s (6kW, 7/45°C)	0.38L/s (8kW, 7/45°C)
Nominal system flow cooling ($\Delta T=5K$)	0.29L/s (6kW, 35/7°C)	0.34L/s (7.1kW, 35/7°C)

External circulation pump must be used when the pressure drop in the system is greater than the available external pressure. In such case, a bypass line with non-return valve must be installed.

Use an overflow valve if system flow cannot be guaranteed.

Indoor unit	HMS60-W	HMS100-W
Outdoor unit	FDCW60VNX-W	FDCW71VNX-W
Highest recommended supply / return temperature	55/45°C	
Max. pressure, climate system	0.3MPa (3.0bar)	
Max. temperature, climate system	65°C	
Max. temperature in indoor unit	65°C	
Max. temperature from external heat source	65°C	
Max. supply temperature with compressor	58°C	60°C
Min. supply temperature cooling	7°C	
Max. supply temperature cooling	25°C	
Min. volume, climate system without under floor cooling application	50L	80L
Min. volume, climate system with under floor cooling application	50L	80L
Max. flow, climate system	0.29L/s	0.38L/s
Min. flow, climate system	0.09L/s	0.19L/s
Nominal system flow heating ($\Delta T=5K$)	0.29L/s (6kW, 7/45°C)	0.38L/s (8kW, 7/45°C)
Nominal system flow cooling ($\Delta T=5K$)	0.29L/s (6kW, 35/7°C)	0.34L/s (7.1kW, 35/7°C)

External circulation pump must be used when the pressure drop in the system is greater than the available external pressure. In such case, a bypass line with non-return valve must be installed.

Use an overflow valve if system flow cannot be guaranteed.