



UNIDAD INTERIOR FANCOIL SUELO TECHO CON CARCASA



	HTW-FST-27DA	HTW-FST-36DA	HTW-FST-45DA	HTW-FST-54DA	HTW-FST-72DA	HTW-FST-90DA	HTW-FST-108DA	HTW-FST-126DA
CÓDIGO EAN	8435483852266	8435483852273	8435483852280	8435483852297	8435483852303	8435483852310	8435483852327	8435483852334

Alimentación eléctrica **V, F, HZ** 220-240V (1 Fase ~ 50Hz)

RENDIMIENTO

		kW	2,70	3,60	4,50	5,40	7,20	9,00	10,80	12,60
Capacidad refrigeración ¹	Velocidad max	kW	2,70	3,60	4,50	5,40	7,20	9,00	10,80	12,60
		Frg/h	2322	3096	3870	4644	6192	7740	9288	10836
	Velocidad mínima	kW	1,74	2,33	2,91	3,49	4,65	5,81	6,97	8,14
		Frg/h	1500	2000	2499	2999	3998	4998	5998	6997
Capacidad Calefacción ²	Velocidad max	kW	4,05	5,40	6,75	8,10	10,80	13,50	16,20	18,90
		Kcal/h	3483	4644	5805	6966	9288	11610	13932	16254
	Velocidad mínima	kW	2,51	3,35	4,19	5,02	6,70	8,37	10,05	11,72
		Kcal/h	2159	2880	3600	4321	5759	7200	8640	10080
Consumo	W	28	34	42	55	77	85	115	142	

CARACTERÍSTICAS

Caudal de aire	Velocidad máxima	m ³ /h	510	680	850	1020	1360	1700	2040	2380
	Velocidad mínima	m ³ /h	260	340	430	510	680	850	1020	1190
Presión sonora	Vel. (M/Med./B)	dB(A)	39	41	43	45	46	48	50	51
Caudal de agua		m ³ /h	0,46	0,62	0,77	0,93	1,23	1,54	1,85	2,16
Presión máxima de trabajo		bar	16	16	16	16	16	16	16	16
Pérdida de carga		bar	0,15	0,18	0,23	0,28	0,3	0,22	0,3	0,36

Intercambiador Cu + Al hidrofílico

DIMENSIONES Y PESO

Dimensiones netas	mm	908*250*496	1058*250*496	1208*250*496	1258*250*496	1608*250*496	1758*250*496	1908*250*496	2058*250*496
Peso neto	Kg	21,1	23,8	26,2	28	40,7	43,2	46	49,5

CONEXIONES

Conexiones de agua	ida/Retorno	"	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
Drenaje		mm	Ø 21	Ø 21	Ø 21	Ø 21	Ø 21	Ø 21	Ø 21	Ø 21